
Product Specification

CO0W-30

Fully Synthetic Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO0W30-1	CO0W30-4	CO0W30-5	CO0W30-20	CO0W30-60	CO0W30-200

LEVELS OF QUALITY

The lubricant CO0W-30 complies with the following international specifications:

API SN/CF; ACEA C2, C3; BMW LONG LIFE 04; FIAT 9.55535.DS1, GS1; FORD WSS-M2C950-A; JAGUAR LAND ROVER STJLR.03.5007; MB 229.5; OPEL DEXOS 02; VW 504.00-507.00; PORSCHE C30; RENAULT RN0700, RN0710

DESCRIPTION

CO0W-30 is a LONG LIFE 100% synthetic lubricant with low ash content (MID SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO V and EURO VI emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

CO0W-30 has been specifically designed to satisfy the latest AUDI-Volkswagen, BMW e Mercedes-Benz specifications for motorizations with prolonged service intervals and fitted with particulate filtration systems, are maintenance-free and without fuel additives.

SAE Scale		0W/30
Density at 15°C.Kg/dm ³	ASTM D1298	0.834
Viscosity at 100°C.cSt	ASTM D445	11.6
Viscosity Index	ASTM D2270	168
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-42
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	7.5

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline 0W-30_REV.3 October 2021
