



## Product Specification

### CO10W-30STOU Heavy Duty Mineral Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO10W30STOU-1	CO10W30STOU-4	CO10W30STOU-5	CO10W30STOU-20	CO10W30STOU-60	CO10W30STOU-200

#### LEVELS OF QUALITY

The lubricant CO10W-30STOU complies with the following international specifications:

API CG-4/SF, ACEA E3, API GL-4, MB 228.1, JD J2 7-J20C/D, FORD M2C 159B/C-134D, NH 82009201/2/3, CNH MAT 3525-3526, ZF TE-ML 06A/B, 07B, MF CMD M1145-M1144-1139-1143-1135, MIL L-2104D / L-46152C / L-2105

#### DESCRIPTION

A multigrade and multifunctional oil of STOU type, especially recommended for all types of agricultural diesel engines. The quality of basic oils along with a reliable additive package guarantee an efficient engine cleaning and protection of mechanical components against wear, even under heavy operating conditions, by providing the lubricant with:

- An excellent anti-wear capability,
- Detergent and dispersant power,
- An excellent fluidity at low temperature,
- An excellent oxidation resistance.

#### APPLICATIONS

CO10W-30 S.T.O.U. is a multifunctional product to be used in all agriculture and earthmoving systems, whenever a product complying with newer versions of the specification is required. The following benefits can be obtained, if you use this product:

- A higher engine cleaning,
- A better protection and longer engine life,
- A good cold start.

SAE Scale		10W-30
Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	11.5
Viscosity Index	ASTM D2270	135
Flammability V.A.°C	ASTM D92	205
Pour Point °C	ASTM D97	-27
T.B.N.	ASTM D2896	9

The above mentioned values are indicative of production average values and are not an integral part of the specification.

**TDS Comline 10W-30STOU\_REV.1 March 2013**