



## Product Specification

### CO15W-40CG4 Mineral Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO15W40CG4-1	CO15W40CG4-4	CO15W40CG4-5	CO15W40CG4-20	CO15W40CG4-60	CO15W40CG4-200

#### LEVELS OF QUALITY

The lubricant CO15W-40CG4 complies with the following international specifications:

ACEA E2 A2 B3, API CG-4/CF-4 SJ, MB 228.1, MAN M271, MTU TYPE1, VOLVO VDS, CAT ECF-1-A, MACK EO-M, CUMMINS CES 20076/20071, VW 501.01-505.00

#### DESCRIPTION

CO15W-40CG4 is a 'HPDO' multigrade oil of multifunctional type formulated for naturally aspired or supercharged diesel engines of lorries, buses and earthmoving machines even in heavy duty applications. Furthermore it can be used in diesel and petrol engines of cars and commercial vehicles. The high viscosity index allows its use under any climatic conditions, providing the maximum protection for the engine both at cold starts and at high temperatures, ensuring in this way the right viscosity even for long distances.

CO15W-40CG4 offers a high detergent and dispersant power, an excellent resistance to corrosion and oxidation and a high antifoam power. The following benefits can be obtained, if you use this product:

- A higher engine cleaning,
- A better protection against piston ring sticking,
- A reduced bore polishing (exhaust pipe polishing),
- More protection against wear.

It is recommended to observe always the oil change interval as suggested by the car manufacturer.

SAE Scale		15W-40
Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.880
Viscosity at 100°C.cSt	ASTM D445	14.00
Viscosity Index	ASTM D2270	135
Flammability V.A.°C	ASTM D92	220
Pour Point °C	ASTM D97	-27
T.B.N.	ASTM D2896	11

The above mentioned values are indicative of production average values and are not an integral part of the specification.

**TDS Comline 150W-40CG4\_REV.2 March 2020**

Comline Auto Parts Ltd

Unit B1 Luton Enterprise Park, Sundon Park Road, Luton, Bedfordshire, LU3 3GU, Great Britain

T: +44 1582 578 888 | F: +44 1582 578 889