

## Product Specification

### COATF3G Semi-Synthetic Transmission Fluid

1 L	4 L	5 L	20 L	60 L	200L
COATF3G-1	COATF3G-4	COATF3G-5	COATF3G-20	COATF3G-60	COATF3G-200

#### LEVELS OF QUALITY

The lubricant COATF3G complies with the following international specifications:

GM DEXRON III - IIIG, MB 236.5-236.9, ZF TE-ML 02F, 03D, 04D, 09B, 11B, 14A, 17C, VOITH G607, FORD MERCON V ALLISON C-4 CAT TO-2, MAN339 TYP V1

#### DESCRIPTION

COMLINE COATF3G is a fluid produced using carefully selected and balanced components and recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a product able to satisfy the requirements of GENERAL MOTORS Dexron III. It is also used as an hydraulic oil over a large temperature range for applications in the automotive, industry and marine field.

#### APPLICATIONS

It ensures excellent performances in terms of:

- Frictional properties;
- Thermal-oxidative stability;
- Wear and corrosion resistance;
- Foaming resistance;
- Compatibility with components for automatic transmissions, elastomer seals and plastic parts.

Thanks to the above mentioned features and to a high viscosity index it also ensures an excellent cold fluidity, by maintaining the desired viscosity at high temperatures.

Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.860
Colour		Red
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	150
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-30

The above mentioned values are indicative of production average values and are not an integral part of the specification.

**TDS Comline ATF3G\_REV.1 MARCH 2020**

Comline Auto Parts Ltd

Unit B1 Luton Enterprise Park, Sundon Park Road, Luton, Bedfordshire, LU3 3GU, Great Britain

T: +44 1582 578 888 | F: +44 1582 578 889