

Product Specification

COATF3H Fully-Synthetic Transmission Fluid

1 L	4 L	5 L	20 L	60 L	200L
COATF3H-1	COATF3H-4	COATF3H-5	COATF3H-20	COATF3H-60	COATF3H-200

LEVELS OF QUALITY

The lubricant COATF3H complies with the following international specifications:

GM DEXRON III-IIIH-IIE, MB 236.5-236.9-236.10-236. 11-236.12, VOITH G607, ALLISON C-4, CAT TO-2, ZF TE-ML02E,03D,04D, 14B,16L,17C, MAN339 V2/Z2, VOLVO 97341, FORD MERCON V

DESCRIPTION

COATF3H is a fluid based on a synthetic technology which is produced using carefully selected and balanced components and recommended for automatic transmissions, power steering, hydraulically assisted steering and torque converters, whenever it is required a product able to satisfy the requirements of GENERAL MOTORS Dexron III - IIIH - IIE.

It is especially recommended for hydraulic frictions to select the gears within the BMW and Mercedes Benz powershift.

APPLICATIONS

It ensures excellent performances in terms of:

- Frictional properties;
- Thermal-oxidative stability;
- Wear and corrosion resistance;
- Foaming resistance;
- Compatibility with components for automatic transmissions, elastomer seals and plastic parts;
- Extending oil change intervals;
- Fuel economy.

Thanks to the above mentioned features and to a high viscosity index it also ensures an excellent cold fluidity, by maintaining the desired viscosity at high temperatures.

SAE Scale		OATF3H
Density at 15°C.Kg./dm ³	ASTM D1298	0.860
Colour		Amber
Viscosity at 100°C.cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	160
Flammability V.A.°C	ASTM D92	195
Pour Point °C	ASTM D97	-33

The above mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline OATF3H_REV.1 MARCH 2013

Comline Auto Parts Ltd

Unit B1 Luton Enterprise Park, Sundon Park Road, Luton, Bedfordshire, LU3 3GU, Great Britain

T: +44 1582 578 888 | F: +44 1582 578 889